

View Online at <https://aerobasegroup.com/nsn/5985-01-370-4899>

**Overall Length:**

2.000 inches

**Overall Height:**

0.500 inches

**Overall Width:**

1.760 inches

**Frequency Rating:**

1.2 gigahertz single frequency operating and 1.4 gigahertz single frequency operating

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Switch Type:**

Nontransfer

**Distance Between Mounting Facility Centers:**

1.740 inches single mounting facility pattern and 1.760 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.45 single

**Insertion Loss In Decibels:**

1.00 single

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Male

**Minimum Crosstalk Rating In Decibels:**

40.0 single

**Actuator Operating Method:**

Relay

**Switching Time:**

1.0 microseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

1

**Coupling Position Quantity:**

2

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Material:**

Stainless steel connecto (s)

**Precious Material And Location:**

Contact surfaces gold and outer case silver

**Precious Material:**

Gold and silver

**Surface Treatment:**

Paint body outside surfaces and silver body outside surfacespassivate connecto (s) all surfacesgold contact(s) all surfaces

**Terminal Type And Quantity:**

2 plug, coaxial and 3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0