## NSN 5985-01-372-2513

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-372-2513

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.100 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.825 inches
Overall Height:
1.000 inches
Overall Width:
1.880 inches
Operating Tempurature Range:
-20.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.10 and 1.40
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.75
Overall Attenuation Range In Decibels:
+0.0/+45.5
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
0.5 and 1.0 and 2.0 and 4.0 and 10.0 and 20.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 megahertz and 750.000 megahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:

7 pushbutton

## NSN 5985-01-372-2513

Variable Attenuator - Page 2 of 2



## Mounting Facility Pattern: Four position rectangular Mounting Facility Screw Thread Diameter: 0.112 inches Impedance Rating In Ohms: 50.0 input-output Mounting Thread Tolerance Class: 2b internal Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A223a0