

View Online at <https://aerobasegroup.com/nsn/5985-01-372-6847>

Body Style:

Rectangular

Overall Length:

3.320 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Frequency Rating:

2.2 gigahertz single frequency operating and 2.3 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.177 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.800 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.800 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

1.0 watts average single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.45 dc

Actuator Voltage In Volts:

28.0

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

3

Coupling Position Quantity:

12

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position in-line single mounting facility pattern

Criticality Code Justification:

Feat

Special Features:

Wires shall be terminated with a m24308/4-2f connector; wire length 6 in. Measured from terminal to connector backshell

Terminal Type And Quantity:

4 plug, coaxial and 8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0