

View Online at <https://aerobasegroup.com/nsn/5985-01-372-8868>

Body Style:

Rectangular

Overall Length:

2.140 inches

Overall Height:

2.180 inches

Overall Width:

1.362 inches

Frequency Rating:

0.0 gigahertz 1st frequency operating and 3.0 gigahertz 1st frequency operating 3.0 gigahertz 2nd frequency operating and 8.0 gigahertz 2nd frequency operating 8.0 gigahertz 3rd frequency operating and 12.4 gigahertz 3rd frequency operating 12.4 gigahertz 4th frequency operating and 18.0 gigahertz 4th frequency operating

Unthreaded Mounting Hole Diameter:

0.141 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

0.800 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.400 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.800 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.20 1st 1.30 2nd 1.40 3rd 1.50 4th

Insertion Loss In Decibels:

0.20 1st 0.30 2nd 0.40 3rd 0.50 4th

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

75.0 1st 70.0 2nd 60.0 3rd 60.0 4th

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

28.0

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Latching

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Terminal Type And Quantity:

4 plug, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0