

View Online at <https://aerobasegroup.com/nsn/5985-01-372-8870>

Body Style:

Rectangular

Overall Length:

2.972 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Frequency Rating:

0.0 gigahertz single frequency operating and 3.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.172 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.800 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.800 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.24 dc

Actuator Voltage In Volts:

24.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Latching

Pole Quantity:

1

Throw Quantity:

3

Coupling Position Quantity:

5

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Aluminum body stainless steel connecto (s) beryllium contact(s) aluminum cover

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel body all surfaces passivate connecto (s) all surfaces gold contact(s) all surfaces paint cover all surfaces

Terminal Type And Quantity:

4 plug, coaxial and 1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0