NSN 5985-01-372-9550

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-372-9550

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b single flange all connection facilities

Thread Direction:

Right-hand single flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

1

Flange Inside Width:

0.620 inches single flange and 0.624 inches single flange

Flange Inside Height:

0.209 inches single flange and 0.313 inches single flange

Flange Outside Width:

1.610 inches single flange and 1.640 inches single flange

Flange Outside Height:

1.610 inches single flange and 1.640 inches single flange

Flange Depth:

0.360 inches single flange and 0.390 inches single flange

Voltage Standing Wave Ratio:

1.15

Maximum Operating Pressure:

35.0 pounds per square inch gage

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches single flange all connection facilities

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 threaded hole single flange all connection facilities

Flange Style:

Choke type single flange

Waveguide Length:

4.500 inches

Special Features:

100 watts avg power; 160 kw peak power; 12.4 to 18.0 ghz frequency

NSN 5985-01-372-9550

Waveguide Assembly - Page 2 of 2



Flexi	bility:
Rigid	single

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment and flange

Style Designator:

Straight type

Thread Series Designator:

Unc single flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0