# NSN 5985-01-372-9550

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-372-9550

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b single flange all connection facilities

**Thread Direction:** 

Right-hand single flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

1

#### Flange Inside Width:

0.620 inches single flange and 0.624 inches single flange

#### Flange Inside Height:

0.209 inches single flange and 0.313 inches single flange

#### Flange Outside Width:

1.610 inches single flange and 1.640 inches single flange

# Flange Outside Height:

1.610 inches single flange and 1.640 inches single flange

## Flange Depth:

0.360 inches single flange and 0.390 inches single flange

# **Voltage Standing Wave Ratio:**

1.15

#### **Maximum Operating Pressure:**

35.0 pounds per square inch gage

#### **Waveguide Outside Width:**

0.702 inches

# **Thread Size:**

0.138 inches single flange all connection facilities

#### **Waveguide Inside Width:**

0.622 inches

# **Waveguide Inside Height:**

0.311 inches

## **Waveguide Outside Height:**

0.391 inches

## Flange Connecting Facility And Quantity:

4 threaded hole single flange all connection facilities

# Flange Style:

Choke type single flange

## Waveguide Length:

4.500 inches

#### **Special Features:**

100 watts avg power; 160 kw peak power; 12.4 to 18.0 ghz frequency

# NSN 5985-01-372-9550

Waveguide Assembly - Page 2 of 2



Flexi	bility:
Rigid	single

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment and flange

**Style Designator:** 

Straight type

**Thread Series Designator:** 

Unc single flange all connection facilities

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0