## NSN 5985-01-372-9588

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-372-9588

Application Design:
Transmission line
Body Material:
Beryllium copper and copper
Body Style:
Rectangular terminal/terminals on three surfaces
Body Surface Treatment:
Nickel plated and gold plated
Overall Length:
0.735 inches
Overall Height:
0.150 inches
Overall Width:
Between 0.500 inches and 0.530 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.35 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
20.0 watts average
Rf Signal Attenuation In Decibels:
7.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1.0 gigahertz and +1.0/+2.5 gigahertz and +2.5/+4.0 gigahertz
Mounting Method:
Terminal
Terminal Type And Quantity:
2 ribbon and 1 surface contact
Frequency Range:
Between 0.000 gigahertz and 4.000 gigahertz
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-01-372-9588

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000