

View Online at <https://aerobasegroup.com/nsn/5985-01-372-9974>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b all flanges all connection facilities

**Thread Direction:**

Right-hand all flanges all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.896 inches all flanges and 0.904 inches all flanges

**Flange Inside Height:**

0.396 inches all flanges and 0.404 inches all flanges

**Flange Outside Width:**

1.610 inches all flanges and 1.640 inches all flanges

**Flange Outside Height:**

1.610 inches all flanges and 1.640 inches all flanges

**Flange Depth:**

0.423 inches all flanges and 0.453 inches all flanges

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.08

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Thread Size:**

0.164 inches all flanges all connection facilities

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Flange Connecting Facility And Quantity:**

4 threaded hole all flanges all connection facilities

**Flange Style:**

Choke type all flanges

**Waveguide Length:**

Between 1.480 inches and 1.500 inches

**Special Features:**

1200 watts power; 8.0 to 12.4 ghz frequency

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segmentaluminum alloy all flange

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc all flanges all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A073a0