NSN 5985-01-373-3139

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-373-3139

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.340 inches
Bolt Circle Diameter:
2.500 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
3 threaded hole
Frequency Range:
Between 7.800 gigahertz and 8.400 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Three position circular
Mounting Facility Screw Thread Diameter:
0.138 inches
Mounting Thread Tolerance Class:
2b internal
Special Features:
Non-contacting, counter clockwise rotation increases loss; aluminum body; stainless steel connector
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-01-373-3139

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0