NSN 5985-01-374-7088

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-374-7088

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.4075 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Inside Diameter:

1.216 inches all flanges and 1.224 inches all flanges

Flange Depth:

0.422 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Leg Length:

1.510 inches

Waveguide Center To Center Distance:

1.750 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segmentaluminum all flange

NSN 5985-01-374-7088

Waveguide Assembly - Page 2 of 2

Style Designator:

U-bend type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A073a0

