

View Online at <https://aerobasegroup.com/nsn/5985-01-375-6460>

**Cross Sectional Shape:**

Internal, rectangular double ridged external, rectangular

**Thread Class:**

2b all flanges all connection facilities

**Thread Direction:**

Right-hand all flanges all connection facilities

**End Application:**

Aircraft model f-14d

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.795 inches all flanges and 0.801 inches all flanges

**Flange Inside Height:**

0.425 inches all flanges and 0.431 inches all flanges

**Flange Outside Width:**

1.360 inches all flanges and 1.390 inches all flanges

**Flange Outside Height:**

1.360 inches all flanges and 1.390 inches all flanges

**Flange Depth:**

0.250 inches all flanges

**Voltage Standing Wave Ratio:**

1.35

**Insertion Loss In Decibels:**

0.50

**Waveguide Outside Width:**

0.791 inches

**Thread Size:**

0.138 inches all flanges all connection facilities

**Waveguide Inside Width:**

0.691 inches

**Waveguide Inside Height:**

0.321 inches

**Waveguide Outside Height:**

0.421 inches

**Waveguide Longer Offset Distance:**

Between 8.250 inches and 8.510 inches

**Flange Connecting Facility And Quantity:**

4 captive screws all flanges all connection facilities

**Flange Style:**

Contact, double ridge type all flanges

**Waveguide Offset Distance:**

23.970 inches

**Flexibility:**

Flexible all tubing segment or rigid all tubing segment

**Material:**

Aluminum alloy all tubing segment

**Surface Treatment:**

Chromate all tubing segment all surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc all flanges all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0