NSN 5985-01-376-4695

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-376-4695

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
2.550 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.125 inches
Overall Height:
0.750 inches
Overall Width:
1.550 inches
Unthreaded Mounting Hole Diameter:
0.154 inches
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.4
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 250.000 megahertz and 1000.000 megahertz
Adjustment Device Type And Quantity:
1 electronic, current controlled
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Special Features:
The second row of mtg holes are spaced 1.250 in. Apart parallel to width
Terminal Type And Quantity:
3 connector, coaxial, female
Shelf Life:

N/a

NSN 5985-01-376-4695

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0