

View Online at <https://aerobasegroup.com/nsn/5985-01-376-4696>

Application Design:

Transmission line

Body Style:

Irregular

Overall Length:

2.050 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.905 inches

Overall Height:

0.750 inches

Overall Width:

1.300 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Voltage Standing Wave Ratio:

2.00

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.9

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole

Frequency Range:

Between 1000.000 megahertz and 2000.000 megahertz

Adjustment Device Type And Quantity:

1 electronic, current controlled

Mounting Facility Pattern:

Isosceles triangle

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.980 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

3 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A223a0