NSN 5985-01-377-8645

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-377-8645

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.870 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.436 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.768 inches
Overall Height:
1.000 inches
Overall Width:
0.940 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Operating Tempurature Range:
-18.0/+45.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
0.5 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+7.0
Attenuation Accuracy Reference Frequency:
20.0 megahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
3
Attenuation Per Step In Decibels:
1.0 and 2.0 and 4.0
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 0.000 hertz and 20.000 megahertz
Overall Attenuation Accuracy in Decibels:

-0.25/+0.25

NSN 5985-01-377-8645

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:

1 electronic, programmable

Mounting Facility Pattern:

Four position rectangular

Special Features:

6 msec switching speed

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0