## NSN 5985-01-379-5646

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-379-5646

Application Design:				
Transmission line				
Body Material:				
Aluminum alloy				
Body Style:				
1b round, terminal/terminals in opposite surface				
Terminal Material:				
Steel, corrosion resisting				
Terminal Surface Treatment:				
Passivated				
Body Surface Treatment:				
Any acceptable				
Overall Length:				
1.240 inches				
Overall Diameter:				
Between 0.350 inches and 0.385 inches				
Operating Tempurature Range:				
-54.0/+125.0 degrees celsius				
Voltage Standing Wave Ratio:				
1.35				
Input Impedance Rating In Ohms:				
50.0				
Output Impedance Rating In Ohms:				
50.0				
Coaxial Connector Series Designation:				
Sma				
Power Rating:				
0.5 watts average				
Rf Signal Attenuation In Decibels:				
18.0				
Voltage Standing Wave Ratio Frequency Range:				
+2.0/+18.0 gigahertz				
Attenuation Accuracy In Decibels:				
-0.75/+0.75				
Connection Type Per Function:				
Female output and male input				
Mounting Method:				
Connector				
Terminal Type And Quantity:				
2 connector				
Frequency Range:				
Between 2.000 gigahertz and 18.000 gigahertz				

## NSN 5985-01-379-5646

Fixed Attenuator - Page 2 of 2



Fsc	App	lication	Data:
-----	-----	----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000