

View Online at <https://aerobasegroup.com/nsn/5985-01-380-3071>

**Frequency Rating:**

2.0 gigahertz single frequency voltage standing wave ratio and 4.0 gigahertz single frequency voltage standing wave ratio

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.300 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

2.300 inches single mounting facility pattern

**Operating Temperature Range:**

-10.0/+50.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.50 single

**Insertion Loss In Decibels:**

3.00 single

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Female

**Minimum Crosstalk Rating In Decibels:**

60.0 single

**Actuator Operating Method:**

Solid state

**Actuator Voltage In Volts:**

12.0

**Switching Time:**

30.0 nanoseconds

**Switch Return Mechanism Type:**

Fail-safe

**Coupling Position Quantity:**

2

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Terminal Type And Quantity:**

2 solder stud and 1 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0