

View Online at <https://aerobasegroup.com/nsn/5985-01-380-7786>

Frequency Rating:

4.0 gigahertz single frequency voltage standing wave ratio and 8.0 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.125 inches

Longest Horizontal Distance Between Mounting Centers:

2.300 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

2.300 inches single mounting facility pattern

Operating Temperature Range:

-10.0/+50.0 degrees celsius

Voltage Standing Wave Ratio:

1.70 single

Insertion Loss In Decibels:

3.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Solid state

Actuator Voltage In Volts:

12.0

Switching Time:

30.0 nanoseconds

Coupling Position Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Terminal Type And Quantity:

2 solder stud and 1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0