

View Online at <https://aerobasegroup.com/nsn/5985-01-381-0039>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.007 inches second flange and 3.010 inches second flange

Flange Inside Height:

1.507 inches second flange and 1.510 inches second flange

Flange Outside Diameter:

5.298 inches first flange and 5.328 inches first flange

Flange Depth:

1.235 inches second flange and 1.265 inches second flange

Flange Connecting Hole Diameter:

0.257 inches second flange all connection facilities and 0.260 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.20

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

5.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Thread Size:

0.250 inches first flange all connection facilities

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

30.000 inches

Waveguide Center To Center Distance:

4.500 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber single tubing jacket

Surface Treatment:

Chromate zinc all flange outside surfaces and paint all flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0