

View Online at <https://aerobasegroup.com/nsn/5985-01-382-3363>

Application Design:

Printed circuit board

Body Style:

Rectangular, terminals on one surface

Overall Length:

1.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.470 inches

Overall Height:

0.750 inches

Overall Width:

0.760 inches

Bushing Length:

0.600 inches

Voltage Standing Wave Ratio:

1.30

Power Rating:

0.2 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.5

Overall Attenuation Range In Decibels:

+0.0/+20.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 terminal

Frequency Range:

Between 55.000 megahertz and 65.000 megahertz

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Precious Material And Location:

Exterior case surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0