NSN 5985-01-382-5107

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-382-5107

Body Material:
Beryllium copper
Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Material:
Beryllium copper
Terminal Surface Treatment:
Gold plated
Body Surface Treatment:
Nickel plated or gold plated
Overall Length:
0.750 inches
Overall Height:
0.150 inches
Overall Width:
Between 0.495 inches and 0.530 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
40.0 watts average
Rf Signal Attenuation In Decibels:
2.5
Voltage Standing Wave Ratio Frequency Range:
+0.000/+1.225 gigahertz
Attenuation Accuracy In Decibels:
-0.20/+0.20
Terminal Type And Quantity:
3 tab, solder lug
Frequency Range:
Between 0.000 hertz and 1.225 gigahertz
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Shelf Life:
N/a

NSN 5985-01-382-5107

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000