

View Online at <https://aerobasegroup.com/nsn/5985-01-382-5107>

**Application Design:**

Transmission line

**Body Material:**

Beryllium copper

**Body Style:**

Rectangular terminal/terminals on three surfaces

**Terminal Material:**

Beryllium copper

**Terminal Surface Treatment:**

Gold plated

**Body Surface Treatment:**

Nickel plated or gold plated

**Overall Length:**

0.750 inches

**Overall Height:**

0.150 inches

**Overall Width:**

Between 0.495 inches and 0.530 inches

**Voltage Standing Wave Ratio:**

1.20

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Power Rating:**

40.0 watts average

**Rf Signal Attenuation In Decibels:**

2.5

**Voltage Standing Wave Ratio Frequency Range:**

+0.000/+1.225 gigahertz

**Attenuation Accuracy In Decibels:**

-0.20/+0.20

**Terminal Type And Quantity:**

3 tab, solder lug

**Frequency Range:**

Between 0.000 hertz and 1.225 gigahertz

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000