## NSN 5985-01-386-9492

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-386-9492

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
1.240 inches
Overall Diameter:
0.380 inches
Operating Tempurature Range:
-54.0/+100.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 0.2 kilowatts peak
Rf Signal Attenuation In Decibels:
0.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output
·
Unpackaged Unit Weight: 0.800 ounces
Mounting Method: Connector
Terminal Type And Quantity:
2 connector

## NSN 5985-01-386-9492

Fixed Attenuator - Page 2 of 2



Between 0.000 hertz and 12.400 gigahertz

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000