## NSN 5985-01-386-9608

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-386-9608

Application Design:
Transmission line
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Overall Length:
Between 2.140 inches and 2.180 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.480 inches and 0.520 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.080 inches and 1.120 inches
Overall Height:
Between 1.910 inches and 1.950 inches
Overall Width:
Between 0.360 inches and 0.400 inches
Mounting Hole/stud Quantity:
4
Body Length:
Between 1.760 inches and 1.800 inches
Unthreaded Mounting Hole Diameter:
Between 0.102 inches and 0.108 inches
Operating Tempurature Range:
-55.0/+90.0 degrees celsius
End Application:
Test set, antenna an/psm-40
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.9/+2.2 gigahertz
Mounting Method:
Unthreaded hole
Terminal Type And Quantity:
4 connector
Frequency Range:
Between 0.900 gigahertz and 2.200 gigahertz
Shelf Life:
N/a
Unit Of Measure:

## NSN 5985-01-386-9608

Fixed Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A20000

