NSN 5985-01-386-9608

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-386-9608 **Application Design:** Transmission line **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Overall Length:** Between 2.140 inches and 2.180 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 0.480 inches and 0.520 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** Between 1.080 inches and 1.120 inches **Overall Height:** Between 1.910 inches and 1.950 inches **Overall Width:** Between 0.360 inches and 0.400 inches **Mounting Hole/stud Quantity: Body Length:** Between 1.760 inches and 1.800 inches **Unthreaded Mounting Hole Diameter:** Between 0.102 inches and 0.108 inches **Operating Tempurature Range:** -55.0/+90.0 degrees celsius **End Application:** Test set, antenna an/psm-40 **Voltage Standing Wave Ratio:** 1.40 **Coaxial Connector Series Designation:** Rf Signal Attenuation In Decibels: 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.9/+2.2 gigahertz **Mounting Method:** Unthreaded hole **Terminal Type And Quantity:** 4 connector Frequency Range: Between 0.900 gigahertz and 2.200 gigahertz Shelf Life:

N/a

Unit Of Measure:

--

NSN 5985-01-386-9608

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000