## NSN 5985-01-389-1927

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-389-1927

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## **Tubing Wall Construction Style:**

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

0.896 inches first flange

## Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

## Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

## Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

#### Flange Depth:

0.423 inches first flange and 0.443 inches first flange

## **Voltage Standing Wave Ratio:**

1.500

#### **Insertion Loss In Decibels:**

0.230

## **Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

## Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

## Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

## **Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

## Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges first connection facility

## Flange Style:

Cover type first flange

## Flexibility:

Flexible single tubing segment

#### Material:

Copper alloy all tubing segment and flange

## **Style Designator:**

Three bend type

## Shelf Life:

N/a

## **Unit Of Measure:**

--

# NSN 5985-01-389-1927

Waveguide Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A073a0