

View Online at <https://aerobasegroup.com/nsn/5985-01-390-0632>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches all flanges and 2.005 inches all flanges

Flange Inside Height:

1.002 inches all flanges and 1.005 inches all flanges

Flange Outside Diameter:

3.610 inches all flanges and 3.640 inches all flanges

Flange Depth:

0.360 inches all flanges and 0.390 inches all flanges

Flange Connecting Hole Diameter:

0.199 inches all flanges all connection facilities and 0.203 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.08

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

Between 24.750 inches and 25.250 inches

Flexibility:

Flexible single tubing segment

Material:

Copper alloy single tubing segment

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0