

View Online at <https://aerobasegroup.com/nsn/5985-01-390-0645>

Body Style:

Rectangular

Overall Length:

1.500 inches

Overall Height:

1.000 inches

Overall Width:

0.400 inches

Frequency Rating:

20.0 megahertz single frequency voltage standing wave ratio and 2000.0 megahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.106 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.300 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.800 inches single mounting facility pattern

Shortest Vertical Distance Between Mounting Centers:

0.800 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.30 single

Insertion Loss In Decibels:

2.00 3rd

Minimum Crosstalk Rating In Decibels:

75.0 1st

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.012 dc

Actuator Voltage In Volts:

Between 4.75 and 5.25

Switch Operation Sequence:

Makes before breaks

Switching Time:

3.0 microseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0