

View Online at <https://aerobasegroup.com/nsn/5985-01-390-0645>

**Body Style:**

Rectangular

**Overall Length:**

1.500 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.400 inches

**Frequency Rating:**

20.0 megahertz single frequency voltage standing wave ratio and 2000.0 megahertz single frequency voltage standing wave ratio

**Unthreaded Mounting Hole Diameter:**

0.106 inches

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

1.300 inches single mounting facility pattern

**Shortest Horizontal Distance Between Mounting Centers:**

0.800 inches single mounting facility pattern

**Shortest Vertical Distance Between Mounting Centers:**

0.800 inches single mounting facility pattern

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.30 single

**Insertion Loss In Decibels:**

2.00 3rd

**Minimum Crosstalk Rating In Decibels:**

75.0 1st

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

0.012 dc

**Actuator Voltage In Volts:**

Between 4.75 and 5.25

**Switch Operation Sequence:**

Makes before breaks

**Switching Time:**

3.0 microseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

2

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Terminal Type And Quantity:**

4 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0