

View Online at <https://aerobasegroup.com/nsn/5985-01-390-1308>

**Body Style:**

Rectangular

**Overall Length:**

1.875 inches

**Overall Height:**

1.750 inches

**Overall Width:**

0.300 inches

**Frequency Rating:**

0.4 gigahertz single frequency rf power handling and 18.1 gigahertz single frequency rf power handling

**Unthreaded Mounting Hole Diameter:**

0.094 inches

**Switch Type:**

Nontransfer

**Distance Between Mounting Facility Centers:**

0.750 inches 1st mounting facility pattern

**Longest Horizontal Distance Between Mounting Centers:**

0.850 inches single mounting facility pattern

**Shortest Horizontal Distance Between Mounting Centers:**

0.295 inches single mounting facility pattern

**Intermediate Horizontal Distance Between Mounting Centers:**

0.280 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

0.380 inches single mounting facility pattern

**Operating Temperature Range:**

-30.0/+75.0 degrees celsius

**Voltage Standing Wave Ratio:**

2.00 single

**Insertion Loss In Decibels:**

1.50 single

**Rf Power Handling Capability:**

0.75 watts peak single

**Minimum Crosstalk Rating In Decibels:**

40.0 single

**Actuator Operating Method:**

Solid state

**Switch Operation Sequence:**

Makes before breaks

**Switching Time:**

0.5 microseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

2

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position trapezoid single mounting facility pattern

**Terminal Type And Quantity:**

4 pin and 1 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A158a0