

View Online at <https://aerobasegroup.com/nsn/5985-01-390-1308>

Body Style:

Rectangular

Overall Length:

1.875 inches

Overall Height:

1.750 inches

Overall Width:

0.300 inches

Frequency Rating:

0.4 gigahertz single frequency rf power handling and 18.1 gigahertz single frequency rf power handling

Unthreaded Mounting Hole Diameter:

0.094 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.750 inches 1st mounting facility pattern

Longest Horizontal Distance Between Mounting Centers:

0.850 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.295 inches single mounting facility pattern

Intermediate Horizontal Distance Between Mounting Centers:

0.280 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.380 inches single mounting facility pattern

Operating Temperature Range:

-30.0/+75.0 degrees celsius

Voltage Standing Wave Ratio:

2.00 single

Insertion Loss In Decibels:

1.50 single

Rf Power Handling Capability:

0.75 watts peak single

Minimum Crosstalk Rating In Decibels:

40.0 single

Actuator Operating Method:

Solid state

Switch Operation Sequence:

Makes before breaks

Switching Time:

0.5 microseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position trapezoid single mounting facility pattern

Terminal Type And Quantity:

4 pin and 1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0