NSN 5985-01-392-6235

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-392-6235
Application Design:
Waveguide
Body Material:
Metal
Body Style:
10b round, terminal/terminals on opposite surfaces
Overall Length:
1.240 inches
Overall Diameter:
Between 0.350 inches and 0.385 inches
Inside Width:
0.307 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Inside Height:
0.307 inches
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
40.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.20/+0.20
Connection Type Per Function:
Female input and male output
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-a-3933/14 government specification

N/a

Shelf Life:

NSN 5985-01-392-6235

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000