## NSN 5985-01-393-0367

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-393-0367
Application Design:
Transmission line
Body Material:
Aluminum alloy, qq-a-250/11, alloy 6061, t6
Body Style:
Err-090
Terminal Material:
Steel, corrosion resisting
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Anodized
Overall Length:
Between 3.160 inches and 3.220 inches
Overall Diameter:
Between 1.470 inches and 1.530 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.30 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
20.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.75/+0.75
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

## NSN 5985-01-393-0367

Fixed Attenuator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000