NSN 5985-01-395-9925

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-395-9925

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless third tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches all flanges and 0.904 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Voltage Standing Wave Ratio:

1.30

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Waveguide Fifth Leg Length:

1.310 inches

Flange Style:

Choke type all flanges

Waveguide Sixth Leg Length:

1.350 inches

NSN 5985-01-395-9925

Waveguide Assembly - Page 2 of 2



Flexibility: Rigid third tubing segment Material: Aluminum alloy third tubing segment **Precious Material And Location:** Flex all surfaces silver **Precious Material:** Silver Surface Treatment: Silver second tubing segment all surfaces Style Designator: Five bend type **Thread Series Designator:** Unc all flanges all connection facilities **Specification Data:** 82577-8655424 manufacturers source control Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A073a0