NSN 5985-01-396-1097

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-396-1097

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Training set, electronic warfare an/mst-t (v)

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

2.835 inches all flanges and 2.845 inches all flanges

Flange Inside Height:

1.335 inches all flanges and 1.345 inches all flanges

Flange Outside Width:

4.448 inches all flanges and 4.520 inches all flanges

Flange Outside Height:

2.980 inches all flanges and 3.020 inches all flanges

Flange Depth:

0.670 inches all flanges and 0.710 inches all flanges

Flange Connecting Hole Diameter:

0.257 inches all flanges all connection facilities and 0.262 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.03

Maximum Operating Pressure:

8.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Waveguide First Leg Length:

3.879 inches

Waveguide Fifth Leg Length:

3.850 inches

Flange Style:

Contact type all flanges

NSN 5985-01-396-1097 Waveguide Assembly - Page 2 of 2



Waveguide Second Leg Length:	
3.900 inches	
Waveguide Sixth Leg Length:	
1.643 inches	
Waveguide Third Leg Length:	
3.900 inches	
Waveguide Fourth Leg Length:	
8.100 inches	
Flexibility:	
Rigid all tubing segment	
Material:	
Aluminum alloy all tubing segment and flange	
Surface Treatment:	
Chromate all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces	
Style Designator:	
Five bend type	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A073a0	