

View Online at <https://aerobasegroup.com/nsn/5985-01-396-2981>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches second flange and 1.126 inches second flange

Flange Inside Height:

0.493 inches first flange and 0.501 inches first flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

0.166 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

18.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

22.350 inches

Waveguide Center To Center Distance:

9.300 inches

Special Features:

8.0-8.5 ghz operating frequency

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0