

View Online at <https://aerobasegroup.com/nsn/5985-01-396-2992>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches second flange and 0.904 inches second flange

Flange Inside Height:

0.396 inches second flange and 0.404 inches second flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

7.800 inches

Waveguide Center To Center Distance:

3.880 inches

Flexibility:

Rigid third tubing segment

Material:

Copper alloy second tubing segment

Precious Material And Location:

Inside surfaces silver

Precious Material:

Silver

Surface Treatment:

Nickel second tubing segment outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange all connection facilities

Specification Data:

82577-8655429 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0