## NSN 5985-01-396-7922

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-396-7922

| View Online at https://aerobasegroup.com/nsn/5985-01-396-7922 |
|---|
| Application Design:   |
| Transmission line   |
| Body Style:   |
| Coaxial type  |
| Overall Length:   |
| 1.750 inches  |
| Overall Height:   |
| 1.875 inches  |
| Overall Width:  |
| 3.125 inches  |
| Distance Between Mounting Facility Centers:                   |
| 2.750 inches  |
| Voltage Standing Wave Ratio:                                  |
| 1.50 and 1.65   |
| Coaxial Connector Series Designation:                         |
| Sma   |
| Power Rating:   |
| 2.0 watts average and 0.2 kilowatts peak                      |
| Mounting Facility Screw Thread Series Designator:             |
| Unc   |
| Overall Attenuation Range In Decibels:                        |
| +0.0/+69.0  |
| Attenuation Variation Method:                                 |
| Stepped   |
| Step Position Quantity:                                       |
| 69  |
| Attenuation Per Step In Decibels:                             |
| 1.0   |
| Mounting Facility Type And Quantity:                          |
| 2 threaded hole   |
| Frequency Range:  |
| Between 0.000 hertz and 18.000 gigahertz                      |
| Mounting Thread Quantity:                                     |
| 40 per inch   |
| Adjustment Device Type And Quantity:                          |
| 2 thumbscrew  |
| Mounting Facility Pattern:                                    |
| Two position in-line  |
| Mounting Facility Screw Thread Diameter:                      |
| 0.112 inches  |
| Impedance Rating In Ohms:                                     |
|   |

50.0 input-output

## NSN 5985-01-396-7922

Variable Attenuator - Page 2 of 2



## Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0