## NSN 5985-01-396-8999

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-396-8999

Application Design:				
Transmission line				
Body Material:				
Brass				
Body Style:				
Err-090				
Body Surface Treatment:				
Any acceptable				
Overall Length:				
2.700 inches				
Overall Diameter:				
0.840 inches				
Operating Tempurature Range:				
-55.0/+125.0 degrees celsius				
Voltage Standing Wave Ratio:				
1.15 and 1.20 and 1.25				
Input Impedance Rating In Ohms:				
50.0				
Output Impedance Rating In Ohms:				
50.0				
Coaxial Connector Series Designation:				
N				
Power Rating:				
2.0 watts average				
Rf Signal Attenuation In Decibels:				
6.0				
Voltage Standing Wave Ratio Frequency Range:				
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz				
Attenuation Accuracy In Decibels:				
-0.10/+0.10				
Connection Type Per Function:				
Female input and male output				
Mounting Method:				
Connector				
Terminal Type And Quantity:				
2 connector				
Frequency Range:				
Between 0.000 hertz and 12.400 gigahertz				
Specification Data:				
81349-mil-a-3933 government specification				
Shelf Life:				
N/a				

## NSN 5985-01-396-8999

Fixed Attenuator - Page 2 of 2



Init	<i>(</i> )+	Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

Mil-std (military Standard):

Mil-a-3933 spec.