NSN 5985-01-396-8999

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-396-8999

| Application Design: | | | | |
|--|--|--|--|--|
| Transmission line | | | | |
| Body Material: | | | | |
| Brass | | | | |
| Body Style: | | | | |
| Err-090 | | | | |
| Body Surface Treatment: | | | | |
| Any acceptable | | | | |
| Overall Length: | | | | |
| 2.700 inches | | | | |
| Overall Diameter: | | | | |
| 0.840 inches | | | | |
| Operating Tempurature Range: | | | | |
| -55.0/+125.0 degrees celsius | | | | |
| Voltage Standing Wave Ratio: | | | | |
| 1.15 and 1.20 and 1.25 | | | | |
| Input Impedance Rating In Ohms: | | | | |
| 50.0 | | | | |
| Output Impedance Rating In Ohms: | | | | |
| 50.0 | | | | |
| Coaxial Connector Series Designation: | | | | |
| N | | | | |
| Power Rating: | | | | |
| 2.0 watts average | | | | |
| Rf Signal Attenuation In Decibels: | | | | |
| 6.0 | | | | |
| Voltage Standing Wave Ratio Frequency Range: | | | | |
| +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz | | | | |
| Attenuation Accuracy In Decibels: | | | | |
| -0.10/+0.10 | | | | |
| Connection Type Per Function: | | | | |
| Female input and male output | | | | |
| Mounting Method: | | | | |
| Connector | | | | |
| Terminal Type And Quantity: | | | | |
| 2 connector | | | | |
| Frequency Range: | | | | |
| Between 0.000 hertz and 12.400 gigahertz | | | | |
| Specification Data: | | | | |
| 81349-mil-a-3933 government specification | | | | |
| Shelf Life: | | | | |
| N/a | | | | |

NSN 5985-01-396-8999

Fixed Attenuator - Page 2 of 2



| | | |
|------|-------------|----------|
| Init | <i>(</i>)+ | Measure: |
| | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

Mil-std (military Standard):

Mil-a-3933 spec.