NSN 5985-01-397-3322 Waveguide Switch - Page 1 of 2



- vaveguide Switch Tage Tot 2	arvup
View Online at https://aerobasegroup.com/nsn/5985-01-397-3322	
Thread Class:	
2b mounting facility hole	
Body Style:	
Rectangular	
Overall Length:	
9.530 inches	
Overall Height:	
4.250 inches	
Overall Width:	
4.250 inches	
Frequency Rating:	
2.43 gigahertz single frequency operating and 3.41 gigahertz single frequency operating	
Switch Type:	
Transfer	
Distance Between Mounting Facility Centers:	
3.200 inches single mounting facility pattern	
Longest Horizontal Distance Between Mounting Centers:	
3.200 inches single mounting facility pattern	
Longest Vertical Distance Between Mounting Centers:	
3.200 inches single mounting facility pattern	
Operating Tempurature Range:	
-40.0/+125.0 degrees celsius	
End Application:	
Training set, electronic warfare an/mst-t (v)	
Voltage Standing Wave Ratio:	
1.10 single	
Insertion Loss In Decibels:	
0.05 single	
Rf Power Handling Capability:	
10.0 watts average 1st	
Minimum Crosstalk Rating In Decibels:	
80.0 single	
Actuator Current Type And Rating In Amps:	
2.0 dc	
Actuator Voltage In Volts:	
Between 22.0 and 32.0	

Switching Time:

200.0 milliseconds

Switch Return Mechanism Type:

Latching

Waveguide Flange Type:

Contact

NSN 5985-01-397-3322

Waveguide Switch - Page 2 of 2



Coupling Position Quantity:	
3	
Mounting Facility Type And Quantity:	
4 threaded hole	
Гhread Size:	
0.250 inches mounting facility hole	
Mounting Facility Pattern:	
Four position rectangular single mounting facility pattern	
Flange Connecting Facility And Quantity:	
3 unthreaded hole	
Material:	
Aluminum alloy flang (s)	
Surface Treatment:	
Chromate flang (s) all surfaces	
Thread Series Designator:	
Unc mounting facility hole	
Terminal Type And Quantity:	
6 pin	
Shelf Life:	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Filg:	
A158a0	