NSN 5985-01-398-6281

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-398-6281

Ap	plication	Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

2.870 inches

Overall Height:

2.000 inches

Overall Width:

0.560 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

5.0 watts average and 3.0 kilowatts peak

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0/+20.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

6 threaded hole

Frequency Range:

Between 2.700 gigahertz and 2.900 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.180 inches

Impedance Rating In Ohms:

50.0 input-output

Special Features:

Two in line mounting holes in front

Terminal Type And Quantity:

2 connector, coaxial, female

NSN 5985-01-398-6281

Variable Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0

