## NSN 5985-01-398-6281

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-398-6281

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.870 inches
Overall Height:
2.000 inches
Overall Width:
0.560 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average and 3.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
6 threaded hole
Frequency Range:
Between 2.700 gigahertz and 2.900 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.180 inches
Impedance Rating In Ohms:
50.0 input-output
Special Features:
Two in line mounting holes in front
Terminal Type And Quantity:

2 connector, coaxial, female

## NSN 5985-01-398-6281

Variable Attenuator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0