NSN 5985-01-398-8303

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-398-8303

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
Between 3.580 inches and 3.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.750 inches
Overall Height:
Between 2.880 inches and 3.120 inches
Overall Width:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.250 inches
Operating Tempurature Range:
-67.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
50.0 watts average and 8.0 kilowatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 2.700 gigahertz and 2.900 gigahertz
Overall Attenuation Accuracy In Decibels:
-2.00/+2.00
Adjustment Device Type And Quantity:
1 shaft

Four position rectangular

NSN 5985-01-398-8303

Variable Attenuator - Page 2 of 2



Shaft Type:

Round, slotted

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0