## NSN 5985-01-399-8678

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-399-8678 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Overall Length:** 0.870 inches **Overall Diameter:** 0.317 inches **Voltage Standing Wave Ratio:** 1.10 and 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 5.0 **Voltage Standing Wave Ratio Frequency Range:** +0.000/+2.000 gigahertz and +2.000/+4.000 gigahertz and +4.000/+8.000 gigahertz and +8.000/+12.400 gigahertz **Connection Type Per Function:** Female output and male input **Mounting Method: Terminal Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz **Test Data Document:** 81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-a-3933/25 government specification Shelf Life: N/a **Unit Of Measure:** 

Yes - demil/mli

**Demilitarization:** 

## NSN 5985-01-399-8678

Fixed Attenuator - Page 2 of 2



Fiig:

A20000