NSN 5985-01-400-0882

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Any acceptable



View Online at https://aerobasegroup.com/nsn/5985-01-400-0882

| Body Style: |
|--|
| Rectangular terminal/terminals on three surfaces |
| Terminal Surface Treatment: |
| Gold plated |
| Overall Length: |
| 0.645 inches |
| Overall Height: |
| 0.035 inches |
| Overall Width: |
| 0.372 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.90 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Power Rating: |
| 0.5 watts average and 100.0 watts peak |
| Rf Signal Attenuation In Decibels: |
| 12.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+12.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.60/+0.60 |
| Mounting Method: |
| Terminal |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Frequency Range: |
| Between 0.000 hertz and 12.000 gigahertz |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| |

NSN 5985-01-400-0882

Fixed Attenuator - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000