NSN 5985-01-400-0882

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Any acceptable



View Online at https://aerobasegroup.com/nsn/5985-01-400-0882

Body Style:
Rectangular terminal/terminals on three surfaces
Terminal Surface Treatment:
Gold plated
Overall Length:
0.645 inches
Overall Height:
0.035 inches
Overall Width:
0.372 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.90
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
0.5 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
12.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.0 gigahertz
Attenuation Accuracy In Decibels:
-0.60/+0.60
Mounting Method:
Terminal
Terminal Type And Quantity:
3 tab, solder lug
Frequency Range:
Between 0.000 hertz and 12.000 gigahertz
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a

NSN 5985-01-400-0882

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000