

View Online at <https://aerobasegroup.com/nsn/5985-01-400-1659>

Application Design:

Transmission line

Body Material:

Metal

Body Style:

Err-090

Overall Length:

0.087 inches

Overall Diameter:

0.317 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.10 and 1.15 and 1.20 and 1.25 and 1.35

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

0.5

Voltage Standing Wave Ratio Frequency Range:

+0.0/+2.0 gigahertz and +2.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Test Data Document:

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-a-3933/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000