# NSN 5985-01-400-1659

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-400-1659

## Application Design:

Transmission line

## **Body Material:**

Metal

## Body Style:

Err-090

### **Overall Length:**

0.087 inches

#### **Overall Diameter:**

0.317 inches

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Voltage Standing Wave Ratio:

1.10 and 1.15 and 1.20 and 1.25 and 1.35

### Input Impedance Rating In Ohms:

#### 50.0

**Output Impedance Rating In Ohms:** 

50.0

**Coaxial Connector Series Designation:** 

Sma

## **Power Rating:**

2.0 watts average and 500.0 watts peak

### **Rf Signal Attenuation In Decibels:**

0.5

# Voltage Standing Wave Ratio Frequency Range:

+0.0/+2.0 gigahertz and +2.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

## **Connection Type Per Function:**

Female input and male output

## **Mounting Method:**

Connector

# Terminal Type And Quantity:

2 connector

## Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

# Test Data Document:

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-a-3933/25 government specification

Shelf Life:

N/a

## Unit Of Measure:

# NSN 5985-01-400-1659

Fixed Attenuator - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A20000

