NSN 5985-01-406-3707

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-406-3707

| | Online at https://aerobasegroup.com/nsn/5985-01-406-3707 |
|---------|--|
| Appli | cation Design: |
| Trans | mission line |
| Body | Style: |
| Coaxi | al type |
| Overa | all Length: |
| 4.110 | inches |
| Overa | all Height: |
| 0.870 | inches |
| Overa | all Width: |
| 1.630 | inches |
| End A | Application: |
| F-15 c | depot |
| Coaxi | al Connector Series Designation: |
| Mm | |
| Powe | r Rating: |
| 1.0 wa | atts average and 50.0 watts peak |
| Insert | tion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.08 | |
| Overa | all Attenuation Range In Decibels: |
| +0.0/+ | -11.0 |
| Atten | uation Variation Method: |
| Stepp | ed |
| Step | Position Quantity: |
| 11 | |
| Atten | uation Per Step In Decibels: |
| 1.0 | |
| Moun | ting Facility Type And Quantity: |
| Free s | standing base |
| Frequ | iency Range: |
| Betwe | een 0.000 gigahertz and 26.500 gigahertz |
| Overa | all Attenuation Accuracy In Decibels: |
| -0.03/ | +0.03 |
| Adjus | stment Device Type And Quantity: |
| 1 knol | b w/dial |
| Impeo | dance Rating In Ohms: |
| 50.0 iı | nput-output |
| Termi | inal Type And Quantity: |
| 2 coni | nector, coaxial, female |
| Shelf | Life: |
| N/a | |
| Unit (| Df Measure: |

NSN 5985-01-406-3707

Variable Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A223a0

